

specifications

	GSM DC™	GSM G-Power	GSM G-Power SL	M-105 Digital w/battery tester	M-105 Digital DC w/battery tester
Code	33122	OR033124	OR033125	OR033126	OR033128
Type	Wireless ultrasonic	Wireless ultrasonic	Wireless ultrasonic	Wireless ultrasonic	Wireless ultrasonic
Activation	Automatic	Automatic	Automatic	Upon connection/switch	Upon connection/switch
Transmission	PTT	PTT	PTT	PTT	PTT
Receiving	Automatic	Automatic	Automatic	Automatic	Automatic
Speaker volume adjustment	No	Yes	Yes - separate headset	Yes	Yes
System type	H-SSB	H-SSB	H-SSB	H-SSB	H-SSB
Frequency	32.768 KHz ch. 2 41.000 KHz	32.768 KHz	32.768 KHz	32.768 KHz	32.768 KHz ch. 2 41.000 KHz
Working range(*)	200m/600ft	500m/1500ft	500m/1500ft	200m/600ft	200m/600ft
Rated depth(**)	40m/120ft	40m/120ft	40m/120ft	Surface unit	Surface unit
Powered by	9V alkaline	9V alkaline	9V alkaline	Rechargeable 6V lead	Rechargeable 6V lead
Autonomy(total)	9h	25h	25h	48h	48h
Low battery autonomy (after alarm starts)	1h	1h	1h	1.5h	1.5h
Low battery alarm	1 beep/30 sec under 7.5V	1 beep/30 sec under 6.8V	1 beep/30 sec under 6.8V	1 beep/30 sec under 4.8V	1 beep/30 sec under 4.8V
DAT™	Yes	No	No	No	No
Transmit/receive cycle	Yes, DAT™ mode-30 sec transmit-20 sec receive	No	No	No	No
Squelch	Automatic	Automatic	Automatic	Automatic	Automatic
Weight with batteries	370g/12.9 oz	370g/12.9 oz	370g/12.9 oz	2.3kg/5 lbs	2.3kg/5 lbs

(*) The operating distance is affected by obstacles, air bubbles, thermo-clines, temperature and salinity

(**) Does not include other depth limits that may apply